Magnum 3 Three Seater

Waiting Chair

Without arms.

Floor

Grouting.

Magnum 4 Four Seater

Without arms.

Floor Grouting.

overall width = 2325±10 mm.

be made up of high quality cold rolled MS perforated sheet of 1.2mm thick,

pressed and welded to form the shape. The seat and back electrostatically coated with epoxy powder and then cured under heat to allow it to form a skin. The base structure shall be supported by MS powder coated with 40-60µ (DFT).

There shall be PPCP shoe provided at the base to avoid scratches on the

floor. The Bench shall be grouted on the floor onto with the legs with the help of Bolts for strength and support. The seat size shall be 440±10 mm(D) X 405±10 mm(H) from ground. Overall height shall be = 775±10 mm, overall depth

= 710±10 mm & overall width = 1765±10 mm.

Supplying & Placing four seater bench without arms. The seat and back shall be made of high quality cold rolled MS perforated sheet of 1.2mm thick, pressed and welded to form the shape. The seat and back electrostatically coated with

epoxy powder and then cured under heat to allow it to form a skin. The base Waiting Chair structure shall be supported by MS powder coated with 50-60µ (DFT). There

> shall be PPCP shoe provided at the base to avoid scratches on the floor. The Bench shall be grouted on the floor onto with the legs with the help of Bolts for strength and support. The seat depth shall be = 440±10 mm and seat height =

405±10 mm. Overall height shall be = 775±10 mm, overall depth = 710±10 mm &